



SAFETY DATA SHEET

Issue Date 27-Apr-2006

Revision Date 31-May-2013

Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name Control Low Odor Mastic Remover

Other Means of Identification

SDS # GI-006

UN/ID No NA1993

Product Code 19105

Recommended Use of the Chemical and Restrictions on Use

Recommended Use Mastic remover.

Details of the Supplier of the Safety Data Sheet

Supplier Address

Grayling Industries, Inc.
1008 Branch Drive
Alpharetta, GA 30004

Emergency Telephone Number

Company Phone Number 1-800-635-1551

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Inhalation (Vapors)	Category 3
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 4

Signal Word

DANGER

Hazard Statements

Toxic if inhaled
Causes skin irritation
Causes serious eye irritation
May be fatal if swallowed and enters airways
Combustible liquid



Appearance Water white liquid

Physical State Liquid

Odor Aromatic

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep cool

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 IF ON SKIN: Wash with plenty of soap and water
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash it before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a POISON CENTER or doctor/physician
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed
 May be harmful in contact with skin

Other Hazards

Toxic to aquatic life with long lasting effects
 Toxic to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Aliphatic Hydrocarbon Solvent	64742-88-7	Proprietary
2-Butoxyethanol	111-76-2	Proprietary
Naphtha (petroleum), heavy aromatic	64742-94-5	Proprietary
Ethoxylated Nonylphenol	9016-45-9	Proprietary

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First Aid Measures

Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
Skin Contact	Wash with soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. Get medical attention if irritation occurs.
Inhalation	After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Have patient lie down and keep warm. Call a physician or poison control center immediately.

Most Important Symptoms and Effects, both Acute and Delayed

Symptoms	Skin contact can lead to drying, defatting, itching, stinging and irritation. May cause severe irritation with redness, pain, and blurred vision. Overexposure by inhalation may cause CNS depression- drowsiness, dizziness, confusion or loss of coordination. May cause nausea, vomiting, stomach ache, and diarrhea.
-----------------	--

Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physicians	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use fire extinguishers with class B extinguishing agents. Carbon dioxide (CO2). Foam.

Unsuitable Extinguishing Media Water spray may be ineffective. If water is used, fog nozzles are preferable.

Specific Hazards Arising from the Chemical

Cool surrounding equipment, fire-exposed containers, and structures with water.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO2).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions	Use personal protective equipment as required.
Other Information	Keep unnecessary and unprotected personnel from entering.
Environmental Precautions	See Section 12 for additional ecological information.

Methods and Material for Containment and Cleaning Up

Methods for Containment	Stop the flow of material, if this is without risk. Dike and contain spill.
Methods for Cleaning Up	Absorb spillage with non-combustible, absorbent material. Mop up and dispose of spilled material.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Advice on Safe Handling

Avoid breathing vapors or mists. Use only with adequate ventilation. Use personal protection recommended in Section 8. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Wash face, hands, and any exposed skin thoroughly after handling. Do not get in eyes, on skin, or on clothing. Avoid free fall of liquid. Ground/bond container and receiving equipment. Do not flame, cut, braze weld or melt empty containers. Emptied container retains product residue. Observe all labeled safeguards until container is cleaned, reconditioned or destroyed.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Store large amounts in structures made for OSHA Class IIIA liquids. Keep containers closed when not in use and upright to prevent leakage. Store locked up.

Incompatible Materials

Strong oxidizing agents. Permanganates. Chromates. Peroxides.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³

Appropriate Engineering Controls

Engineering Controls

Apply technical measures to comply with the occupational exposure limits. Showers. Eyewash stations.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection

Wear approved safety goggles.

Skin and Body Protection

Use impervious gloves. An apron or other impermeable body protection is suggested. Wear suitable protective clothing and footwear appropriate for the risk of exposure.

Respiratory Protection

Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2).

General Hygiene Considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Take off all contaminated clothing and wash it before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	Liquid	Odor	Aromatic
Appearance	Water white liquid	Odor Threshold	Not determined
Color	Water white		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	174-196 °C / 346-385 °F	
Flash Point	60 °C / 141 °F	Tag Closed Cup Lowest Component
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	n/a-liquid	
Upper Flammability Limits	Not determined	
Lower Flammability Limit	0.9%	
Vapor Pressure	0.5 mm Hg	@20°C
Vapor Density	5.0	(Air=1)
Relative Density (Specific Gravity)	0.807	(1=Water) @ 68°F (20°C)
Water Solubility	Appreciable	
Solubility in Other Solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition Temperature	260 °C / 500 °F	Lowest Component
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	
Additional Information	Refractive Index: 1.438	
	Mixed Aniline Point (Acid Insol): 63°C/147°F	
VOC Content (%)	99%	
VOC Content	796.1 g/L	
Density	6.719 lbs/gal	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Heat, flames and sparks.

Incompatible Materials

Strong oxidizing agents. Permanganates. Chromates. Peroxides.

Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO₂).

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information

- Eye Contact** Causes serious eye irritation.
- Skin Contact** Causes skin irritation. May be harmful in contact with skin.
- Inhalation** Toxic if inhaled.
- Ingestion** May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Aliphatic Hydrocarbon Solvent 64742-88-7	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
2-Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 2270 mg/kg (Rat) = 220 mg/kg (Rabbit)	= 2.21 mg/L (Rat) 4 h = 450 ppm (Rat) 4 h
Naphtha (petroleum), heavy aromatic 64742-94-5	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h
Ethoxylated Nonylphenol 9016-45-9	= 1310 mg/kg (Rat)	= 2 mL/kg (Rabbit)	-

Information on Physical, Chemical and Toxicological Effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Carcinogenicity Not classifiable as a human carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol 111-76-2	A3	Group 3		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

Aspiration Hazard May be fatal if swallowed and enters airways.

Numerical Measures of Toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic organisms Toxic to aquatic life with long lasting effects

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Aliphatic Hydrocarbon Solvent 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static		100: 48 h Daphnia magna mg/L EC50
2-Butoxyethanol 111-76-2		1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50		1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50
Naphtha (petroleum), heavy aromatic 64742-94-5	2.5: 72 h Skeletonema costatum mg/L EC50	19: 96 h Pimephales promelas mg/L LC50 static 2.34: 96 h Oncorhynchus mykiss mg/L LC50 1740: 96 h Lepomis macrochirus mg/L LC50 static 45: 96 h Pimephales promelas mg/L LC50 flow-through 41: 96 h Pimephales promelas mg/L LC50		0.95: 48 h Daphnia magna mg/L EC50

Persistence and Degradability

Not determined

Bioaccumulation

Not determined

Mobility

Chemical Name	Partition Coefficient
2-Butoxyethanol 111-76-2	0.81
Naphtha (petroleum), heavy aromatic 64742-94-5	2.9 - 6.1

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances. DOT Ground - "Non-bulk shipments may be non-regulated per 49CFR 173.150(f)(2)".

DOT
UN/ID No NA1993
Proper Shipping Name Combustible liquid, n.o.s. (Petroleum distillates)
Hazard Class Comb Liq
Packing Group III

IATA Not regulated

IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Listed
DSL Listed
EINECS Listed
ENCS Listed
KECL Listed
AICS Listed

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*
- ENCS - Japan Existing and New Chemical Substances*
- IECSC - China Inventory of Existing Chemical Substances*
- KECL - Korean Existing and Evaluated Chemical Substances*
- PICCS - Philippines Inventory of Chemicals and Chemical Substances*

US Federal Regulations

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard Yes

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
2-Butoxyethanol - 111-76-2	111-76-2	Proprietary	1.0

US State Regulations

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Aliphatic Hydrocarbon Solvent 64742-88-7	X		
2-Butoxyethanol 111-76-2	X	X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards 2	Flammability 2	Instability 0	Special Hazards Not determined
<u>HMIS</u>	Health Hazards 3	Flammability 2	Physical Hazards 0	Personal Protection Not determined

Issue Date 27-Apr-2006
 Revision Date 31-May-2013
 Revision Note New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet